

# FLOWCOMPUTER

WITH TEMPERATURE COMPENSATION FOR  
CORRECTED LIQUID VOLUME



## Advantages

- Robust IP67 (NEMA Type4X) field enclosure. It is so rugged, **you can even stand on it!**
- Intrinsically Safe available - ATEX and IECEx approval for gas and dust applications.
- Programming can be done by your own crew, with the sensible menu-driven structure, saving cost and irritation. **Know one, know them all!**
- Very diverse mounting possibilities: walls, pipes, panels or directly onto outdoor sensors!

## Features

- Calculates compensated flow rate, total and accumulated total.
- Displays actual line temperature.
- Selectable on-screen engineering units; volumetric or mass.
- 7 digit resettable total.
- 11 digit accumulated total.
- Explosion/flame proof available.
- Full Modbus communication RS232/485/TTL.
- Loop or battery powered, 8 - 24V AC/DC or 115 - 230V AC power supply.
- Sensor supply 3 / 8.2 / 12 / 24V DC.

## Signal output

- (o)4 - 20mA / 0 - 10V DC according to compensated flow rate.
- Scaled pulse output according to accumulated total.

## Signal input

### Flow

- Ability to process all types of flowmeter signals: Reed-switch, NAMUR, NPN/PNP pulse, Sine wave (coil), Active pulse signals, (o)4 - 20mA, 0 - 10V DC.

### Temperature

- PT100 - 2 or 3 wire.
- (o)4 - 20mA / 0 - 10V DC.

## Applications

- The F-Series is your first and safest choice for field mount indicators in safe and hazardous area applications. Especially in harsh weather conditions like rain, snow, salty atmospheres and temperatures between -40°C up to +80°C (-40°F up to 176°F).
- Applications where nett flow calculation at base conditions is desired without the influence of thermal product expansion. For DIN panel mount indicators, check our D-Series.

## General information

### Introduction

The flowcomputer Model F126-EL has been developed to calculate corrected liquid volume at normal conditions for generic products. The corrected volumetric flow is calculated by using the thermal expansion coefficient algorithm stored in the flowcomputer. The reference temperature can be defined as desired, e.g. 15°C, 20°C or 60°F. A typical application is flow calculation of water, fuel or chemicals at base conditions.

### Display

The display has large 17mm (0.67") and 8mm (0.31") digits which can be set to show flow rate, total and temperature. On-screen engineering units are easily configured from a comprehensive menu. The accumulated total can register up to 11 digits and is backed-up in EEPROM memory every minute.

### Configuration

All configuration settings are accessed via a simple operator menu which can be password protected. Each setting is clearly indicated with an alphanumeric description, which avoids confusing abbreviations and baffling codes. Once familiar with one F-series product, you will be able to program all models in the series without a manual. All settings are safely stored in EEPROM memory in the event of sudden power failure.

### Analog output signal

The calculated flow rate is re-transmitted with the (0)4 - 20mA or 0 - 10V DC output signal. The output signal is updated eight times per second with a filter function being available to smoothen out the signal if desired.

The output value is user defined in relation to the flow rate, e.g. 4mA equals to 15Nm<sup>3</sup>/Hr and 20mA equals to 2000Nm<sup>3</sup>/Hr. The output signal can be passive, active or isolated where the passive output type will loop power the F126-EL as well.

### Pulse output

The scaleable pulse output, reflects the count on the accumulated display. The pulse length is user defined from 0.001 second up to 9.999 seconds. The maximum output frequency is 500Hz. The output signal can be passive NPN, active PNP or an isolated electro-mechanical relay.

### Signal input

The flowcomputer measures the uncorrected volumetric flow and actual line temperature. The F126-EL will accept most pulse and analog input signals for flow. The analog flow input is available with linear and square root calculation and even as 4 - 20mA input loop powered. For temperature measurement, 2 or 3 wire PT100 elements or sensors with a (0)4 - 20mA / 0 - 10V DC output signal can be used.

### Communication

All process data and settings can be read and modified manually or through the Modbus communication link (RS232 / RS485). Full Modbus functionality remains available for the Intrinsically Safe version (TTL).


### Hazardous areas

This model has been ATEX and IECEx certified Intrinsically Safe for gas and dust applications, with an allowed ambient temperature of -40°C to +70°C (-40°F to +158°F). A flame proof Ex d enclosure with ATEX certification is also available.

### Enclosures


Various types of enclosures can be selected, all ATEX and IECEx approved. As standard the F126-EL is supplied in an GRP panel mount enclosure, which can be converted to an IP67 / NEMA Type4X GRP field mount enclosure by the addition of a back case. Most popular is our rugged aluminum field mount enclosure with IP67 / NEMA Type4X rating. Both European or U.S. cable gland entry threads are available.

## Overview application F126-EL



## Dimensions enclosures


### Aluminum & GRP panel mount enclosure



HB & HC enclosures


panel cut-out

### Aluminum & GRP field / wall mount enclosures




#### Aluminum


#### GRP




HA




HD




HL




HE




HM




HF




HN




HG




HO




HH




HP




HJ




HT




HK



HU




HV



HZ

## Terminal connections





### Display example - 90 x 40mm (3.5" x 1.6")




Typical wiring diagram F126-P-(AP)-CH-EL-(OT)-PB-(PX)-TP

Typical wiring diagram F126-P-AP-CH-EL-OT-PX-TA




Typical wiring diagram F126-P-AI-CI-EL-OA-PD-TA



\*Supply voltage: 1.2 / 3.2 / 8.2 / 12 / 24V DC to sensor

Typical wiring diagram F126-A-AA-CB-EL-OX-PM-TP



\*Supply voltage: 3.2 / 8.2 / 12 / 24V DC to sensor



## Hazardous area applications

The F126-EL-XI has been certified according ATEX and IECEx by DEKRA for use in Intrinsically Safe applications with an ambient temperature of -40°C to +70°C (-40°F to +158°F).


- The ATEX markings for gas and dust applications are:

**II 1 G Ex ia IIB/IIC T4 Ga**  
**II 1 D Ex ia IIIC T100 °C Da.**

- The IECEx markings for gas and dust applications are: **Ex ia IIC/IIB T4 Ga** and **Ex ia IIIC T100 °C Da.**


It is allowed to connect up to four barriers in IIB/IIC applications or one barrier in IIC applications. Consult the certificate for the maximum input and output values of the circuits. Full functionality of the F126-EL remains available, including 4 - 20mA output according to the flow rate and Modbus communication (type CT). Power supply type PD-XI offers a 8.2V sensor supply e.g. for one Namur sensor and a temperature sensor. An ATEX approved flame proof Ex d enclosure is available as well. Please contact your supplier for further details.

## Certificate of conformity KEMA 03ATEX1074 X • IECEx DEK 11.0042X




## Configuration example IIB / IIC and IIC

### F126-P-(AP)-(CT)-EL-(OT)-PC-TP-XI - Battery powered unit




## Configuration example IIB / IIIC and IIC - F126-P-AP-(CT)-EL-OT-(PX)-TP-XI - Output loop powered



\* Note sensor supply voltage: 1.2V DC for coil sensors or 3.2V DC for other pulse sensors.


Configuration example IIB / IIIC and IIC - F126-A-AF-(CT)-EL-OX-PD-TA-XI - Power requirement 16 - 30V DC



\* Note power supply type PD: the supply voltage to pulse sensors is maximum 8.7V (Uo=max 8.7V Io=max 25mA Po=max 150mW) and to analog sensors as connected to terminal 1 (internally linked).



Configuration example IIB / IIIC - F126-A-AF-CT-EL-OX-(PC)-(PD)-TA-XI - Power requirement 16 - 30V DC or battery powered



\* Note power supply type PD: the supply voltage to pulse sensors is maximum 8.7V (U<sub>o</sub>=max 8.7V I<sub>o</sub>=max 25mA P<sub>o</sub>=max 150mW) and to analog sensors as connected to terminal 1 (internally linked).

## Technical specification

### General

Display	
Type	High intensity reflective numeric and alphanumeric LCD, UV-resistant.
Dimensions	90 x 40mm (3.5" x 1.6").
Digits	Seven 17mm (0.67") and eleven 8mm (0.31") digits. Various symbols and measuring units.
Refresh rate	User definable: fast, 1sec, 3sec, 15sec, 30sec, off.
Option ZB	Transflective LCD with white LED-backlight. Good readings in full sunlight and darkness.
Note ZB	Only available for safe area applications.

### Ambient temperature

Safe areas	-40°C to +80°C (-40°F to +176°F).
Intrinsically Safe	-40°C to +70°C (-40°F to +158°F).

### Power requirements

Type AP	Analog output loop powered, 8 - 30V DC. Power consumption max 0.5 Watt.
Type PB	Long life Lithium battery - life-time depends upon settings and configuration - up to 5 years. (requires PD, PL or PX)
Type PC	Intrinsically Safe long life lithium battery - life-time depends upon settings and configuration - up to 5 years. (requires XI and PD or PX)
Type PD	8 - 24V AC / DC ± 10%. Power consumption max. 10 Watt. Intrinsically Safe: 16 - 30V DC; power consumption max. 0.75 Watt.
Type PF	24V AC / DC ± 10%. Power consumption max. 15 Watt.
Type PL	Input loop powered from sensor signal 4 - 20mA (type "A") - requires types AI and OT (not Xi).
Type PM	115 - 230V AC ± 10%. Power consumption max. 15 Watt.
Type PX	8 - 30V DC. Power consumption max. 0.5 Watt.
Type ZB	12 - 24V DC ± 10%. Power consumption max. 1 Watt.
Note PB/PF/PM	Not available Intrinsically Safe.
Note PF/PM	The total consumption of the sensors and outputs may not exceed 400mA @ 24V.
Note	For Intrinsically Safe applications, consult the safety values in the certificate.

### Sensor excitation

Type PB/PC/PX	3V DC for pulse signals and 1.2V DC for coil pick-up.
Note	This is not a real sensor supply. Only suitable for sensors with a very low power consumption like coils (sine wave) and reed-switches.
Type PD	1.2 / 3 / 8.2 / 12 / 24V DC - max. 50mA @ 24V DC.
Type PD-XI	1.2 / 3 / 8.2V DC - max. 7mA @ 8.2V DC and mains power supply voltage (as connected to terminal 1).
Note	In case PD-XI and signal A or U: the sensor supply voltage is according to the power supply voltage connected to terminal 1. The sensor supply of the second analog input is fixed 8.2V DC.
Type PF / PM	1.2 / 3 / 8.2 / 12 / 24V DC - max. 400mA @ 24V DC.

### Terminal connections

Type	Removable plug-in terminal strip. Wire max. 1.5mm <sup>2</sup> and 2.5mm <sup>2</sup> .
------	---

### Directives & Standards

EMC	Directive 2014/30/EU, FCC 47 CFR part 15.
Low voltage	Directive 2014/35/EU
RoHS	Directive 2011/65/EU
ATEX / IECEx	Directive 2014/34/EU, IEC 60079-0, IEC 60079-11.
IP & NEMA	EN 60529 & NEMA 250

### Data protection

Type	EEPROM backup of all settings. Backup of running totals every minute. Data retention at least 10 years.
Password	Configuration settings can be password protected.

### Enclosure

General	
Window	Polycarbonate window.
Sealing	Silicone.
Control keys	Three industrial micro-switch keys. UV-resistant silicone keypad.

### Aluminum wall / field mount enclosures

General	Die-cast aluminum wall/field mount enclosure IP67 / NEMA Type4X with 2-component UV-resistant coating.
Dimensions	130 x 120 x 75mm (5.12" x 4.72" x 2.95") - W x H x D.
Weight	1100 gr.
Type HA	Cable entry: 2 x PG9 and 1 x M20.
Type HL	Cable entry: 3 x 1/2" NPT.
Type HM	Cable entry: 2 x M16 and 1 x M20.
Type HN	Cable entry: 1 x M20.
Type HO	Cable entry: 2 x M20.
Type HP	Cable entry: 6 x M12.
Type HT	Cable entry: 1 x 1/2" NPT.
Type HU	Cable entry: 3 x 1/2" NPT.
Type HV	Cable entry: 4 x M20.
Type HZ	Cable entry: no holes.

### GRP wall / field mount enclosures



General	GRP wall/field mount enclosure IP67 / NEMA Type4X, UV-resistant and flame retardant.
Dimensions	130 x 120 x 75mm (5.12" x 4.72" x 2.95") - W x H x D.
Weight	600 gr.
Type HD	Cable entry: no holes.
Type HE	Cable entry: 2 x Ø 16mm and 1 x Ø 20mm.
Type HF	Cable entry: 1 x Ø 22mm (7/8").
Type HG	Cable entry: 2 x Ø 20mm.
Type HH	Cable entry: 6 x Ø 12mm.
Type HJ	Cable entry: 3 x Ø 22mm (7/8").
Type HK	Flat bottom, cable entry: no holes.

### Panel mount enclosures


Dimensions	130 x 120 x 60mm (5.12" x 4.72" x 2.36") - W x H x D.
Panel cut-out	115 x 98mm (4.53" x 3.86") L x H.
Type HB	Die-cast aluminum panel mount enclosure IP65 / NEMA Type4X.
Weight	600 gr.
Type HC	GRP panel mount enclosure IP65 / NEMA Type4X, UV-resistant and flame retardant.
Weight	450 gr.

### Hazardous area

#### Intrinsically Safe (Type XI)

ATEX certification	 II 1 G Ex ia IIB/IIC T4 Ga. II 1 D Ex ia IIIC T100 °C Da.
IECEx certification	 Ex ia IIC/IIB T4 Ga. Ex ia IIIC T100 °C Da.
Ambient Ta	-40°C to +70°C (-40°F to +158°F).

#### Explosion proof (Type XF)

ATEX certification	 II 2 G / Ex d IIB T5 Gb. II 2 D / Ex t IIIB T100 °C Db.
Type XF	Dimensions of enclosure: 300 x 250 x 200mm (11.8" x 9.9" x 7.9") L x H x D.
Weight	Appr. 15kg.
Note	IECEx available on request.

## Signal inputs

Flowmeter	
Type P	Coil / sine wave (HI: 20mVpp or LO: 80mVpp - sensitivity selectable), NPN/PNP, open collector, reed-switch, Namur, active pulse signals 8 - 12 and 24V DC.
Frequency	Minimum 0Hz - maximum 7kHz for total and flow rate. Maximum frequency depends on signal type and internal low-pass filter. E.g. reed switch with low-pass filter: max. frequency 120Hz.
K-Factor	0.000010 - 9,999,999 with variable decimal position.
Low-pass filter	Available for all pulse signals.
Option ZF	coil sensitivity 10mVpp.
Type A	(0)4 - 20mA. Analog input signal can be scaled to any desired range within 0 - 20mA.
Type U	0 - 10V DC. Analog input signal can be scaled to any desired range within 0 - 10V DC.
Accuracy	Resolution: 14 bit. Error < 0.025mA / ± 0.125% FS. Low level cut-off programmable.
Span	0.000010 - 9,999,999 with variable decimal position.
Update time	Four times per second.
Voltage drop	Type A: 2.5V @ 20mA.
Load impedance	Type U: 3kOhm.
Relationship	Linear and square root calculation.
Note	For signal type A and U: external power to sensor is required; e.g. type PD.

Temperature	
Accuracy	Resolution: 14 bit. Error < 0.025mA / ± 0.125% FS. Low level cut-off programmable.
Update time	Four times per second.
Type TA	(0)4 - 20mA. Analog input signal can be scaled to any desired range within 0 - 20mA.
Span	0.000010 - 9,999,999 K with variable decimal position.
Offset	0.00 - 99,999.99 K.
Voltage drop	2.5V @ 20mA.
Type TP	2 or 3 wire PT100.
Range	-100°C to +200°C (-148°F to 392°F). Accuracy 3°C (5.4°F).
Option ZV	Range: -200°C to +800°C (-328°F to 1832°F). Accuracy 3°C (5.4°F).
Type TU	0 - 10V DC. Analog input signal can be scaled to any desired range within 0 - 10V DC.
Span	0.000010 - 9,999,999 K with variable decimal position.
Offset	0.00 - 99,999.99 K.
Load impedance	3kOhm.
Note 1	For signal TA and TU: power supply to temperature sensor is required; e.g. PD.

## Signal outputs

Analog output	
Function	Transmitting compensated flow rate.
Accuracy	10 bit. Error < 0.05%. Analog output signal can be scaled to any desired range.
Update time	Eight times per second.
Type AA	Active 4 - 20mA output (requires PD, PF, PM or PX).
Type AB	Active 0 - 20mA output (requires PD, PF, PM or PX).
Type AF	Passive floating 4 - 20mA output for Intrinsically Safe applications (requires XI + PD or PX).
Type AI	Passive galvanically isolated 4 - 20mA output - also available for battery powered models.
Type AP	Passive 4 - 20mA output - not isolated. Unit will be loop powered.
Type AU	Active 0 - 10V DC output (requires PD, PF, PM or PX).

Digital output	
Function	Pulse output - transmitting accumulated total.
Frequency	Max. 500Hz. Pulse length user definable between 0.001 second up to 9.999 seconds.
Type OA	One active 24V DC transistor output (PNP); max. 50mA per output (requires -PD, PF, PM or PX).
Type OR	One electro-mechanical relay output - isolated; max. switch power 230V AC (N.O.) - 0.5A per relay (requires PF or PM).
Type OT	One passive transistor output (NPN) - not isolated. Max. 50V DC - 300mA per output.
Note:	Digital output only available for Type: P (pending for Type: A / U)

Communication option	
Function	Reading display information, reading / writing all configuration settings.
Protocol	Modbus RTU.
Speed	1200 - 2400 - 4800 - 9600 baud.
Addressing	Maximum 255 addresses.
Type CB	RS232
Type CH	RS485 2-wire
Type CI	RS485 4-wire
Type CT	TTL Intrinsically Safe.

## Operational

Accumulated total	
Digits	11 digits.
Units / decimals	According to selection for total.
Note	Can not be reset to zero.

Line temperature	
Digits	6 digits.
Units	°C, °F or K.
Decimals	1.

Operator functions	
Displayed functions	<ul style="list-style-type: none"> <li>Compensated flow rate.</li> <li>Compensated total and accumulated total.</li> <li>Actual line temperature.</li> <li>Total can be reset to zero by pressing the CLEAR-key twice.</li> </ul>

Total	
Digits	7 digits.
Units	L, m <sup>3</sup> , GAL, USGAL, kg, lb, bbl, no unit.
Decimals	0 - 1 - 2 or 3.
Note	Total can be reset to zero.

Flow rate	
Digits	7 digits.
Units	mL, L, m <sup>3</sup> , Gallons, kg, Ton, lb, bl, cf, RND, ft <sup>3</sup> , scf, Nm <sup>3</sup> , NL, igal - no units.
Decimals	0 - 1 - 2 or 3.
Time units	/sec - /min - /hr - /day.

Flow equations	
Type EL	Corrected liquid volume.
Formula	$Q_{\text{normal}} = Q \times (1 + \alpha (T_{\text{normal}} - T))$ where $\alpha$ = thermal expansion coefficient.
Normal temp.	Default: 273.15 K - any temperature can be set.

# Ordering information

Standard configuration: F126-P-AP-CX-EL-HC-OT-PX-TA-XX-ZX.

Ordering information:	F126	-	A	-C	-EL	-H	-O	-P	-T	-X	-Z
<b>Flowmeter input signal</b>											
A	⊗	(0)4 - 20mA input. (Digital output is pending)									
P		<b>Pulse input: coil, npn, pnp, namur, reed-switch.</b>									
U	⊗	0 - 10V DC input. (Digital output is pending)									
<b>Analog output signal</b>											
AA		Active 4 - 20mA output - requires PD, PF, PM or PX.									
AB		Active 0 - 20mA output - requires PD, PF, PM or PX.									
AF	⊗	I.S. floating 4 - 20mA output - requires XI + PD or PX.									
AI		Isolated 4 - 20mA output.									
AP	⊗	<b>Passive 4 - 20mA output, loop powered unit.</b>									
AU		Active 0 - 10V DC output - requires PD, PF, PM or PX.									
<b>Communication</b>											
CB		Communication RS232 - Modbus RTU.									
CH		Communication RS485 - 2wire - Modbus RTU.									
CI		Communication RS485 - 4 wire - Modbus RTU.									
CT	⊗	Intrinsically Safe TTL - Modbus RTU.									
CX	⊗	<b>No communication.</b>									
<b>Flow equations</b>											
EL	⊗	<b>Corrected liquid volume.</b>									
<b>Panel mount enclosures - IP65 / NEMA Type4X</b>											
HB	⊗	Aluminum enclosure.									
HC	⊗	<b>GRP enclosure.</b>									
<b>GRP field / wall mount enclosures - IP67 / NEMA Type4X</b>											
HD	⊗	Cable entry: no holes.									
HE	⊗	Cable entry: 2 x Ø 16mm & 1 x Ø 20mm.									
HF	⊗	Cable entry: 1 x Ø 22mm (7/8").									
HG	⊗	Cable entry: 2 x Ø 20mm.									
HH	⊗	Cable entry: 6 x Ø 12mm.									
HJ	⊗	Cable entry: 3 x Ø 22mm (7/8").									
HK	⊗	Flat bottom, cable entry: no holes.									
<b>Aluminum field / wall mount enclosures - IP67 / NEMA Type4X</b>											
HA	⊗	Cable entry: 2 x PG9 + 1 x M20.									
HL	⊗	Cable entry: 2 x 1/2"NPT.									
HM	⊗	Cable entry: 2 x M16 + 1 x M20.									
HN	⊗	Cable entry: 1 x M20.									
HO	⊗	Cable entry: 2 x M20.									
HP	⊗	Cable entry: 6 x M12.									
HT	⊗	Cable entry: 1 x 1/2"NPT.									
HU	⊗	Cable entry: 3 x 1/2"NPT.									
HV	⊗	Cable entry: 4 x M20.									
HZ	⊗	Cable entry: no holes.									
<b>Digital output signal</b>											
OA		One active transistor outputs - requires PD, PF, PM or PX.									
OR		One mechanical relay outputs - requires PF or PM.									
OT	⊗	<b>One passive transistor outputs - standard configuration. requires P</b>									
<b>Power requirements</b>											
PD	⊗	8 - 24V AC/DC + sensor supply - with XI: 16 - 30V DC.									
PF		24V AC/DC + sensor supply.									
PL		Input loop powered from sensor signal type "A" - requires AI (not XI).									
PM		115 - 230V AC + sensor supply.									
PX	⊗	<b>Basic power supply 8 - 30V DC (no real sensor supply).</b>									
<b>Additional battery supply (optional)</b>											
PB		Lithium battery powered - requires PD, PL or PX.									
PC	⊗	Lithium battery powered - Intrinsically Safe - requires XI, and PD or PX.									
<b>Temperature input signal</b>											
TA	⊗	<b>(0)4 - 20mA input.</b>									
TP	⊗	PT100 input.									
TU	⊗	0 - 10V DC input.									
<b>Hazardous area</b>											
XI	⊗	Intrinsically Safe, according ATEX and IECEx.									
XF		Ex d enclosure - 3 keys according ATEX.									
XX		<b>Safe area only.</b>									
<b>Other options</b>											
ZB		Backlight.									
ZF	⊗	Coil input 10mVpp.									
ZV	⊗	PRTD-range -200°C / +800°C.									
ZX	⊗	<b>No options.</b>									

The bold marked text contains the standard configuration.

⊗ Available Intrinsically Safe.

Specifications are subject to change without notice.



Quality  
ISO 9001

www.dekra-seal.com

Fluidwell bv

P.O. Box 6  
5460 AA - Veghel - The Netherlands  
Telephone: +31 (0)413 343 786  
Telefax: +31 (0)413 363 443  
email: displays@fluidwell.com  
Internet: www.fluidwell.com

