

F073

Safe area / Intrinsically safe - Level Monitor

with one high / low alarm output



Features

- The display shows the actual level, height or percentage, alarm values, alarm messages and status.
- On-screen engineering units are easily configured from a comprehensive selection.
- Displays clear alarm messages.
- Red flashing LED backlight in case of a level alarm; intensity adjustable.
- Selectable on-screen engineering units for level: ml, L, m³, GAL, USGAL, kg, lb, bbl or no unit.
- Selectable on-screen engineering units for height: mm, cm, m, mtr, inch, ft, mmwk, mmwc, cmwk, cmwc, mwk, mwc, inwc, ftwc, mBar, Bar, PSI or no unit.
- Level: six large 17mm (0.67") digits.
- Level monitoring: two alarm values can be set: low and high level alarm.
- Alarm values can be changed by the operator or they can be password protected.
- One alarm output for high, low or both combined level alarms.
- Intrinsically safe according ATEX, IECEx, FM and CSA C-US.
- GRP, Aluminum or high grade stainless steel enclosure.
- Auto backup of settings in EEPROM memory.
- Easy configuration with clear alphanumeric display.
- Ambient temperature: -40°C to +80°C (-40°F to 176°F).
- Various [accessories](#) are available for this product.

Product description

The F073 is a versatile level indicator with continuous level monitoring feature. It has one low level and one high level alarm value. If desired, an ignore (delay) function can be set up to allow for an incorrect level for a certain period of time. The configuration of the Span, off-set and number of decimals is done through software functions, without any sensitive DIP-switches or trimmers.

Advantages

- Robust aluminum or stainless steel 316L field enclosure (IP65, IP67 / NEMA Type4X) . It is so rugged, a truck can even stand on it!

- Intrinsically Safe available - ATEX, IECEx, FM and CSA approval for gas and dust applications.
- Familiar easy operation with the Fluidwell "Know one, know them all" configuration structure, saving time, cost and aggravation.
- Very diverse mounting possibilities: walls, pipes, panels or directly onto outdoor sensors.

Applications

- Level measurement where continuous level monitoring is important without signal re-transmission.
- The F-Series is your first and best choice for field mount indicators in safe and hazardous area applications. Especially in harsh weather conditions like rain, snow, sandy deserts, salty atmospheres and temperatures between -40°C up to +80°C (-40°F up to 176°F).

Product specifications

Signal Inputs

Level Inputs

- (0)4 – 20mA.
- Reed chain resistance.

Supply

Power Supply

- Long life Lithium battery.
- 4 – 20mA, input Loop-powered.
- 8 – 24V AC/DC.
- 115 – 230V AC.
- Basic: 8 – 30V DC.

Sensor Supply

- 8.2, 12, 24V DC.

Signal Outputs

Alarm outputs

- Function: Configurable alarm output for high, low or both combined level alarms.
- Type: One passive NPN transistor, active PNP transistor or isolated electro-mechanical relay.

Analog outputs

- None.

Hazardous Area

Intrinsically Safe

- ATEX:
Gas: II 1 G Ex ia IIC T4 Ga
Dust: II 1 D Ex ia IIIC T₂₀₀ 100 °C Da
- IECEx:
Gas: Ex ia IIC T4 Ga
Dust: Ex ia IIIC T₂₀₀ 100 °C Da
- CSA & FM:
I.S. Class I/II/III, Div 1, Grp A...G, T4
Class I, Zone 0, AEx ia IIC T4 Ga
Note: Extended aluminum enclosures not available with CSA/FM approval.

Explosion Proof

- ATEX/IECEx:
Gas: II 2 G Ex db IIB+H2 T5 Gb
Dust: II 2 D Ex tb IIIC T80°C Db

Communication

- Modbus communication available on F1-Series products.

- HART communication is available with the F018 Flow rate Monitor / Totalizer.



sales@fluidwell.com | T. +31 (0) 413 - 343 786

We're happy to answer any questions about our products and services.
Just send us an email or give us a call.