


Indicators, controllers and monitoring systems for flow, level, pressure and temperature measurement in industrial environments.

*Count on us.*

## Remote Configuration Quickstart guide

### Getting started


Please start by unzipping the contents of the folder.



Please start the application by double-clicking the RemoteConfiguration.exe. You now have the choice to “connect a device”, or use the tool in “offline configuration” mode.

### Offline Configuration

To use the tool in “offline configuration” mode, please select a device from the dropdown labelled “Model”, and click the “Enter offline configuration” button. You will now be able to create a custom configuration for the selected device.



Indicators, controllers and monitoring systems for flow, level, pressure and temperature measurement in industrial environments.



**FLUIDWELL**  
Accurate Liquid Management

*Count on us.*

In the following example, the “Flowmeter” tab is shown. Each tab has a set of settings that can be changed, corresponding with the manual. You can go through the tabs, and change the settings that need to be changed.

Remote Configuration Tool

Default Config. Load Config. Save Config. Write to device Read device

Current Device: no device detected Status: values need to be read from or written to the devi About...

HOME | Runtime Values | Total | Flow Rate | Display | **Flowmeter** | Analog Output | Pulse Output | Modbus | Datalogging | Others

Signal

NPN  Reed  PNP  Namur  Coil Low  12V dc  
 NPN Low Pass  Reed Low Pass  PNP Low Pass  Coil High  8.1V dc  24V dc

Units (automatic unit conversion)

Hand  Auto volume  Auto mass

Unit

L  US GAL  CF  kg  lb  
 m<sup>3</sup>  I GAL  Oil BBL  ton  US ton

K-Factor

1 Value = 1 pulses / No unit

Decimals K-Factor

0  1  2  3  4  5  6

0 ModMaster: Idle Last Result: None

If you wish to save your custom configuration to your PC, you can select “Save Config.”. You are then able to save the configuration to your PC.

If you want to load an existing configuration, you can choose “Load Config.”. You can then select a previously saved configuration from your PC. To restore the values in the tool to the default configuration for the selected model, please choose “Default Config.”.

Please note the “Write to device” and “Read device” buttons are disabled. They will be enabled when a device is connected.



Fluidwell bv

P.O. Box 6 • 5460 AA • Veghel  
Voltaweg 23 • 5466 AZ • Veghel  
The Netherlands

Telephone: +31 (0) 413 - 343 786  
Telefax: +31 (0) 413 - 363 443  
Email: displays@fluidwell.com  
Internet: www.fluidwell.com

Trade Reg. No: 17120985  
VAT No: NL8085.29.699.B.01  
Bank: ING-Bank  
SWIFT Nr / BIC: INGBNL2A

EUR account no: 66.63.96.078  
IBAN: NL73 INGB 0666 3960 78  
USD account no: 02.20.81.771  
IBAN: NL22 INGB 0022 0817 71


Indicators, controllers and monitoring systems for flow, level, pressure and temperature measurement in industrial environments.

*Count on us.*

## Connecting a device

Please make sure the device is connected to the PC (e.g., accessories ACE01 or ACE02).

If you wish to connect the tool to a device, please enter the “Port Setup” by clicking the “Port Setup” button on the right, on the HOME-tab.



The following window will pop up:

**Port Setup**

Communication setup

COM-port:  show all **COM1**

Bits per second: 9600

Data bits: 8 bits

Parity: None

Stop bits: 1 bit

Release Connect

Status: Connected. Settings: 9600,N,8,1

Modbus setup

Protocol  ASCII  RTU

Slave address: 1

Number of tries: 1

No response timeout (msec): 500

RTU time-out (msec, 0 for default): **20**

Miscellaneous

Lock settings  Always on top  FW300 Mode

Close

Please select the correct COM-port.

Please select the correct speed setting.

Please select the protocol that the device uses. Default is RTU.

Please make sure the RTU time-out is set to 20.

After selecting the correct settings, click the "Connect device" button on the HOME-tab (above the "Port Setup" button).

If you get the following notification, please check if the information entered in the "Port Setup" is compatible with the values found in the device (in the Modbus Communication menu).

**Connect Device**



There was no device found.

OK

Indicators, controllers and monitoring systems for flow, level, pressure and temperature measurement in industrial environments.


*Count on us.*

Once successfully connected, you will get the following notification:



After this, the tool will read the current configuration from the device. When successful, you will see the pop up on the right.

You will be returned to the HOME-tab.



Indicators, controllers and monitoring systems for flow, level, pressure and temperature measurement in industrial environments.


*Count on us.*

From here you can either start configuring your device, restart your device by selecting the “Restart device” button on the right, or read log data (if supported by your device).

An updated configuration can be saved to your PC, or into the device. The “Save Config.” button saves your custom configuration to your PC. You are free to select a location for the file to be saved. The “Write to device” button writes your configuration into the device.

### Reading logdata

When your device supports datalogging, it is possible to read and export this data using the Remote Configuration Tool. When selecting the “Read logdata” button on the HOME-tab, the following window will appear:



First, select the list you would like to read from the dropdown box labelled “Select a log list ...”. Once you have selected a list, click the “Read data” button to start reading the log data.

Indicators, controllers and monitoring systems for flow, level, pressure and temperature measurement in industrial environments.



*Count on us.*

E-Series Configuration - Logdata

Select a log list to read:  
 Runtime Interval [v]    Read data    **Save log data**

##	read;LOGNR;YYYY-MM-DD	HH:MM:SS;FLOWRATE;	TOTAL;	ACC.TOTAL;
0000013;00013;2015-09-08	15:57:00;	0;	0;	0;
0000014;00014;2015-09-08	15:58:00;	0;	0;	0;
0000015;00015;2015-09-08	15:59:00;	0;	0;	0;
0000016;00016;2015-09-08	16:00:00;	0;	0;	0;
0000017;00017;2015-09-08	16:01:00;	0;	0;	0;
0000018;00018;2015-09-08	16:02:00;	0;	0;	0;
0000019;00019;2015-09-08	16:03:00;	0;	0;	0;
0000020;00020;2015-09-08	16:04:00;	0;	0;	0;
0000021;00021;2015-09-08	16:05:00;	0;	0;	0;
0000022;00022;2015-09-08	16:06:00;	0;	0;	0;
0000023;00023;2015-09-08	16:07:00;	0;	0;	0;
0000024;00024;2015-09-08	16:08:00;	0;	0;	0;
0000025;00025;2015-09-08	16:09:00;	0;	0;	0;
0000026;00026;2015-09-08	16:10:00;	0;	0;	0;
0000027;00027;2015-09-08	16:11:00;	0;	0;	0;
0000028;00028;2015-09-08	16:12:00;	0;	0;	0;
0000029;00029;2015-09-08	16:13:00;	0;	0;	0;
0000030;00030;2015-09-08	16:14:00;	0;	0;	0;
0000031;00031;2015-09-08	16:15:00;	0;	0;	0;
0000032;00032;2015-09-08	16:16:00;	0;	0;	0;
0000033;00033;2015-09-08	16:17:00;	0;	0;	0;
0000034;NO RECORD FOUND				

=====  
 End of readout: Runtime Interval - 1234567 - 2015-09-08 16:17:29  
 Total number of retries: 0

After the data has been read, you can save this to your PC. It will be saved as a .csv file, that you can import into, or open with MS Excel.



**Fluidwell bv**  
 P.O. Box 6 • 5460 AA • Veghel  
 Voltaweg 23 • 5466 AZ • Veghel  
 The Netherlands

Telephone: +31 (0) 413 - 343 786  
 Telefax: +31 (0) 413 - 363 443  
 Email: displays@fluidwell.com  
 Internet: www.fluidwell.com


Trade Reg. No: 17120985  
 VAT No: NL8085.29.699.B.01  
 Bank: ING-Bank  
 SWIFT Nr / BIC: INGBNL2A

EUR account no: 66.63.96.078  
 IBAN: NL73 INGB 0666 3960 78  
 USD account no: 02.20.81.771  
 IBAN: NL22 INGB 0022 0817 71

Indicators, controllers and monitoring systems for flow, level, pressure and temperature measurement in industrial environments.



*Count on us.*



The device also saves a number of different events. In the image above some event codes are listed.

Possible events:

FACTORY	Factory defaults
RESTART	Restart
ERRORS	Error
VAR BUS	Variable changed via communication
VAR DIS	Variable change via menu/display
TOT CLR	Total cleared



Quality  
ISO 9001  
www.dekra.nl

Fluidwell bv

P.O. Box 6 • 5460 AA • Veghel  
Voltaweg 23 • 5466 AZ • Veghel  
The Netherlands

Telephone: +31 (0) 413 - 343 786

Telefax: +31 (0) 413 - 363 443

Email: [displays@fluidwell.com](mailto:displays@fluidwell.com)

Internet: [www.fluidwell.com](http://www.fluidwell.com)

Trade Reg. No: 17120985

VAT No: NL8085.29.699.B.01

Bank: ING-Bank

SWIFT Nr / BIC: INGBNL2A

EUR account no: 66.63.96.078

IBAN: NL73 INGB 0666 3960 78

USD account no: 02.20.81.771

IBAN: NL22 INGB 0022 0817 71